

# **TV SERIES-FT 2-1824**

EAN 8422202218243



Reinforced nylon castors, especially indicated to support high-loads up to 700kg (1543lb).

It is used in: internal logistics tools, repair shops, tool trolleys, internal logistics, mobile platforms, transport tools, elevating platforms, food industry, transport carts, logistics for military missions material, ladders, packaging machines, conveyor belts, light machinery for the construction, elevating tables, boilers, cabinetmaker's, locksmith's, metalworks, agricultural farms, meat industry, textile and sport centres.

Mainly used in the industrial sector, aeronautic sector and automobile factories


Suitable for mechanical engineering projects by draftsmen and project executors

FT: castors especially indicated for food and chemical industry applications. Does not leave marks on floor. Reinforced. High resistance to impacts and collisions.

### **Technical Data**

Housing Type	Swivel
Fitting Type	Plate
Braking System	Wheel Brake And Fork
Material	Nylon(Polyamide 6)
Bearing	Plain
Diameter (mm)	150
Width of tyre (mm)	42
Plate dimensions (mm)	139x110
Distance between holes (mm)	105x80
Plate hole diameter (mm)	10
Offset (mm)	133
Overall height (mm)	188
Load	700
Unit Weight of the wheel (kg)	2.75
Volume (cm³)	5067

## CAD



To visualize the image with higher resolution and more technical details, please access to the CAD section



### **Brackets**



Manufactured with pressed steel up to 5 mm. Highly rustresistant double-chrome coating. Double ball bearing reinforced with hardened ball races. Dust-proof in the sealing swivel head. Manufactured to European standard EN 12532.

# **Similar products**





Reinforced nylon (Polyamid 6) wheel, white colour Temperature range:  $-30^{\circ} \div +80^{\circ}$ 

Rolling Resistence Excelent

Noise during the march Reasonable

Floor Protection Reasonable