TV SERIES-FT 2-1829

EAN 8422202218298



Reinforced nylon castors, especially indicated to support high-loads up to 800kg (1764lb).

professional

It is used in: internal logistics tools, repair shops, tool trolleys, internal logistics, mobile platforms, transport tools, elevating platforms, food industry, transport carts, logistics for military missions material, ladders, packaging machines, conveyor belts, light machinery for the construction, elevating tables, boilers, cabinetmaker's, locksmith's, metalworks, agricultural farms, meat industry, textile and sport centres.

Mainly used in the industrial sector, aeronautic sector and automobile factories.


Suitable for mechanical engineering projects by draftsmen and project executors

FT: castors especially indicated for food and chemical industry applications. Does not leave marks on floor. Reinforced. High resistance to impacts and collisions.

Technical Data

Housing Type	Swivel
Fitting Type	Plate
Braking System	Wheel Brake And Fork
Material	Nylon(Polyamide 6)
Bearing	Ball
Diameter (mm)	200
Width of tyre (mm)	42
Plate dimensions (mm)	139x110
Distance between holes (mm)	105x80
Plate hole diameter (mm)	10
Offset (mm)	155
Overall height (mm)	251
Load	800
Unit Weight of the wheel (kg)	3.52
Volume (cm³)	7372

CAD




To visualize the image with higher resolution and more technical details, please access to the CAD section

Product information

TV SERIES-FT 2-1829 (EAN 8422202218298)





Manufactured with pressed steel up to 5 mm. Highly rustresistant double-chrome coating. Double ball bearing reinforced with hardened ball races. Dust-proof in the sealing swivel head. Manufactured to European standard EN 12532.



